

### In the Claims

Please make the following amendments that are provided by replacement claims. The replacement claims are identified by claim number. Marked-up versions of the amendments to the claims follow the remarks section of this response.

SB 7  
A13  
1. (Amended) A Coriolis flowmeter having a reduced flag dimension comprising:

a first flow tube having an inlet end and an outlet end, said first flow tube forming a substantially semicircular arc between said inlet end of said first flow tube and said outlet end of said first flow tube;

a second flow tube having an inlet end and an outlet end, said second flow tube forming a substantially semicircular arc between said inlet end of said second flow tube and said outlet end of said second flow tube;

a driver affixed to said first flow tube at a point on said semicircular arc of said first flow tube that is substantially perpendicular to a bending axis of said first flow tube, said driver also affixed to said second flow tube at a point on said semicircular arc of said second flow tube that is substantially perpendicular to a bending axis of said second flow tube, wherein said driver oscillates said first flow tube and said second flow tube in opposition to each other;

a first brace bar affixed to said first flow tube proximate said inlet end of said first flow tube and affixed to said second flow tube proximate said inlet end of said second flow tube;

a second brace bar affixed to said first flow tube proximate said outlet end of said first flow tube and affixed to said second flow tube proximate said outlet end of said second flow tube; and

pick-offs affixed to said first flow tube on said substantially semicircular arc of said first flow tube and said second flow tube on said substantially semicircular arc of said second flow tube in a position that allows said pick-offs to detect the greatest amount of Coriolis force at a low amplitude vibration.

A13  
2. (Amended) The Coriolis flowmeter of claim 1 further comprising:  
an inlet manifold affixed to said inlet end of said first flow tube and said inlet  
end of said second flow tube to affix said first flow tube and said second flow tube to  
a pipeline.

A14  
4. (Amended) The Coriolis flowmeter of claim 1 further comprising:  
an outlet manifold affixed to said outlet end of said first flow tube and said  
outlet end of said second flow tube to connect said first flow tube and said second  
flow tube to a pipeline.

A15  
6. (Amended) The Coriolis flowmeter of claim 1 further comprising:  
an inlet manifold affixed to said inlet end of said first flow tube and said inlet  
end of said second flow tube to affix said first flow tube and said second flow tube to  
a pipeline;

5 an outlet manifold affixed to said outlet end of said first flow tube and said  
outlet end of said second flow tube to connect said first flow tube and said second  
flow tube to said pipeline; and

a spacer affixed to said inlet manifold and said outlet manifold to maintain a  
fixed distance between said inlet manifold and said outlet manifold.

7. (Amended) The Coriolis flowmeter of claim 6 wherein said spacer  
comprises:

an inlet end affixed to said inlet manifold;

5 an outlet end affixed to said outlet manifold;

a top side, a bottom side, a front side, and a back side each extending  
between said inlet end of said spacer and said outlet end of said spacer to form a  
rectangular body; and

openings through said top side of said spacer through which said first flow  
10 tube and said second flow tube are affixed to said inlet manifold and said outlet  
manifold.

A  
16

9. (Amended) The Coriolis flowmeter of claim 8 wherein said casing comprises:

a front side wall;  
a back side wall; and

5 a mass affixed to said front side wall and said back side wall to change vibrational modes of said casing.

10. (Amended) The Coriolis flowmeter of claim 1 wherein said position of said pick-offs is substantially 25-50 degrees from said bending axis of said first flow tube and said bending axis of said second flow tube.

11. (Amended) The Coriolis flowmeter of claim 10 wherein said position of said pick-offs is 30 degrees from said bending axis of said first flow tube and said bending axis of said second flow tube.